

Factory Direct



DARMANI NORTH AMERICA



Factory Direct

**“Diamond” series Hopper cones**

**NO PILOT CARS NECESSARY**



**See PAMI Test for Aeration Superior results**



DARMANI **“Diamond Series”** STANDARD CONE FEATURES

Diameter	18	21	24	27
Cone -maximum bin size	6415	8910	11828	17056
Heavy Duty Steel Construction	Std.	Std.	Std.	Std.
Designed for long life	Std.	Std.	Std.	Std.
Inspection hatch	Std.	Std.	Std.	Std.
Rack and pinion slide gate	Std.	Std.	Std.	Std.
Outside handle w/bearing slide	Std.	Std.	Std.	Std.
Galvanized sheets	Std.	Std.	Std.	Std.
Galvanized sheet gauge	12/14	12/14	10/12	10/12
Cone slope	40 deg.	40 deg.	40 deg.	40 deg.
Heavy wall legs (5"x5" HSS)	Std.	Std.	Std.	Std.
Quantity of legs	12	14	16	18
Heavy Duty WELDED Beam	Std.	Std.	Std.	Std.
Outer band support	3/8"	3/8"	1/2"	1/2"
Inner band	Yes-¼"	Yes-¼"	Yes-¼"	yes-¼"
2" Angle iron top supports	Std.	Std.	Std.	Std.
Bottom tubular cone support	Std.	Std.	Std.	Std.
Painted	Std.	Std.	Std.	Std.
Slide gate opening size	18"	18"	18"	18"
Discharge height	28"	28"	28"	28"
Overall height	9`5"	10`7"	11`11"	13`10"
<b>Cone weight</b>	<b>4008</b>	<b>6500</b>	<b>7850</b>	<b>9500</b>
Limited warranty	Std.	Std.	Std.	Std.
V-27-Hopper Aeration System	Yes	Yes	Yes	Yes
<b>CROSS AIR MAX FLOW</b>	N/A	N/A	Avail.	Avail.
<b>Structural Steel foundations (Heavy duty 4"x6" HSS tubing)</b>	2 row	3 row	3 row	3 row
<b>Supported by .250 wall tubing</b>	3 row	4 row	4 row	5 row
Wind tie down anchors w/brkt	Yes	Yes	Yes	Yes
HD adjustable anchors w/brkt	Yes	yes	Yes	Yes
HD Cement footing plates	Yes	Yes	Yes	Yes
HD Stiffener mounting brackets	Yes	Yes	Yes	Yes
Hopper to ground ladder	Yes	yes	Yes	Yes
SKYLIFT Mount brackets	Yes	Yes	Yes	yes

SEE HOPPER CONE COMPETITOR COMPARISON GUIDES

[www.darmani.ca](http://www.darmani.ca)

1-866-665-6677

[sales@darmani.ca](mailto:sales@darmani.ca)

CONES SKIDS AIR AIR FANS